

AW 909

| | |
|---------------------------|---|
| TIRE SIZE | 10.0/75 - 15.3 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | HEUPRESSE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 126 A8 |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA-CODE | 94010424 | RC (IN) | 87.7 |
| SW (IN) | 10.8 | RIM REC | 9.00 |
| OD (IN) | 29.9 | ECE | E4-106R-001541 |
| SLR (IN) | 13.5 | PR | 12 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 68 |
|-----------|------|
| 5 FR | 5250 |
| 15 FR | 4460 |
| 20 FR | 4200 |
| 25 FR | 3750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.