


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 900/60 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR DE ALTA POTENCIA / TRACTOR
<b>VERSIÓN</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	195 D

## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94511273	<b>RC (IN)</b>	252.4
<b>SW (IN)</b>	35.4	<b>RIM REC</b>	DW 30B
<b>OD (IN)</b>	84.3	<b>ECE</b>	E11-106R-0010587
<b>SLR (IN)</b>	37.2		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41
45	10240	11950	13410	15110	16820	18530	20720	22190	24370
<b>FROM 40 TO 25</b>	11250	13130	14740	16610	18480	20360	22770	24380	26780
20	11470	13390	15020	16940	18850	20770	23220	24860	27310
12	11710	13660	15320	17270	19220	21170	23680	25350	27850
5	12380	14440	16210	18280	20340	22400	25050	26820	29460
<b>UPTO 20 CYCLIC</b>	12780	14900	16720	18850	20990	23110	25850	27670	30400
<b>UPTO 10 CYCLIC</b>	15240	17790	19960	22510	25040	27580	30850	33020	36290
<b>UPTO 5 CYCLIC</b>	16710	19500	21880	24670	27460	30230	33820	36210	39780
5 HT	11470	13390	15020	16940	18850	20770	23220	24860	27310

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.