


# AGRIMAX V- FLECTO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 710/55 R 34</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ТРАКТОР ВЫСОКОЙ МОЩНОСТИ<br>/ ТРАКТОР-ТЯГАЧ  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 170 D  |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94513376 | <b>RC (IN)</b> | 193.3            |
| <b>SW (IN)</b>  | 27.9     | <b>RIM REC</b> | DW 25 B          |
| <b>OD (IN)</b>  | 65.3     | <b>RIM ALT</b> | DW 27 B          |
| <b>SLR (IN)</b> | 28.6     | <b>ECE</b>     | E11-106R-0010831 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI                            | 9    | 12    | 15    | 17    | 20    | 23    | 29    |
|--------------------------------------|------|-------|-------|-------|-------|-------|-------|
| 45                                   | 5900 | 6860  | 7940  | 8910  | 9870  | 10820 | 12040 |
| <b>FROM 40 TO 25</b>                 | 6480 | 7540  | 8730  | 9790  | 10850 | 11900 | 13230 |
| 20                                   | 6600 | 7680  | 8900  | 9980  | 11060 | 12140 | 13490 |
| 12                                   | 6730 | 7840  | 9070  | 10170 | 11280 | 12380 | 13760 |
| 5                                    | 7120 | 8290  | 9600  | 10760 | 11930 | 13090 | 14550 |
| <b>*UPTO 5 CYC WITH FRONT LOADER</b> | 9070 | 10550 | 12210 | 13700 | 15180 | 16670 | 18520 |
| 5 HT                                 | 6600 | 7680  | 8900  | 9980  | 11060 | 12140 | 13490 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.