

# LG SMOOTH

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>20X10.00 - 10</b>                     |
| <b>UM</b>           | IS STANDARD                              |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                   |
| <b>MACHINERY</b>    | ÅKGRÄSKLIPPARE / LITEN TRAKTOR / TRAKTOR |
| <b>VERSION</b>      | STANDARD                                 |
| <b>TIRE TYPE</b>    | TL                                       |



## DIMENSIONER IS STANDARD

|                 |      |                |                             |
|-----------------|------|----------------|-----------------------------|
| <b>SW (MM)</b>  | 245  | <b>RIM REC</b> | 8.00 I - 55                 |
| <b>OD (MM)</b>  | 500  | <b>RIM ALT</b> | 7.00 I - 55; I - 70; I - 90 |
| <b>SLR (MM)</b> | 223  | <b>ECE</b>     | E11-106R-005202             |
| <b>RC (MM)</b>  | 1450 | <b>PR</b>      | 6                           |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.20</b> |
| 15                | 660         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.