

# FLOTATION 648

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>550/60 - 22.5</b>  |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | BIAS  |
| <b>MACHINERY</b>          | ENFARDADEIRA DE FENO / CEIFEIRA /<br>ESPALHADOR / CEIFEIRA /<br>IMPLEMENTOS AGRÍCOLAS |
| <b>VERSÃO</b>             | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 156 A8/152 B  |
| <b>LI/SS FREE ROLLING</b> | 169 A8/165 B  |



## DIMENSÕES US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CÓDIGO USA</b> | 94045327 | <b>RC (IN)</b> | 146.7          |
| <b>SW (IN)</b>    | 21.7     | <b>RIM REC</b> | AG 16.00       |
| <b>OD (IN)</b>    | 48.8     | <b>ECE</b>     | E4-106R-001565 |
| <b>SLR (IN)</b>   | 21.3     | <b>PR</b>      | 18             |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 44    | 45    | 46    |
|-----------|-------|-------|-------|
| 5 FR      | 17240 | 17580 | 17900 |
| 10 FR     | 15510 | 15820 | 16110 |
| 20 FR     | 13790 | 14060 | 14320 |
| 25 FR     | 12310 | 12550 | 12790 |
| 30 FR     | 11080 | 11300 | 11350 |
| 5 DW      | 11880 | 12110 | 12350 |
| 10 DW     | 10690 | 10900 | 11110 |
| 20 DW     | 9500  | 9690  | 9880  |
| 25 DW     | 8490  | 8650  | 8820  |
| 30 DW     | 7640  | 7790  | 7830  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.