


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 900/65 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATOR DE ALTA POTENCIA / TRATOR
<b>VERSÃO</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	193 D

## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	900	<b>RIM REC</b>	DW 30B
<b>OD (MM)</b>	2338	<b>ECE</b>	E11-106R-0010961
<b>SLR (MM)</b>	1006	<b>SRI</b>	1100
<b>RC (MM)</b>	7003		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	5335	6170	7010	7950	8685	9415	10465
<b>FROM 65 TO 40</b>	5865	6785	7705	8740	9545	10350	11500
30	5980	6920	7855	8910	9735	10555	11730
20	6095	7055	8010	9085	9925	10760	11960
10	6450	7460	8475	9610	10495	11385	12650
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	8215	9500	10790	12240	13365	14490	16100
10HT	5980	6920	7855	8910	9735	10555	11730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.