

AW 708

| | |
|---------------------------|--|
| TIRE SIZE | 400/60 - 15.5 |
| UM | US STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / REBOQUE |
| VERSÃO | HD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 149 A8 |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94052172 | RC (IN) | 100.9 |
| SW (IN) | 15.9 | RIM REC | AG 13.00 |
| OD (IN) | 34.4 | ECE | E11-106R-004253 |
| SLR (IN) | 15.0 | PR | 18 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 65 |
|-----------|-------|
| 5 FR | 10030 |
| 15 FR | 8530 |
| 20 FR | 8020 |
| 25 FR | 7160 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.