

AS 504

TIRE SIZE	10.0/75 - 15.3
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	111 A8
LI/SS FREE ROLLING	123 A8



РАЗМЕРЫ US STANDARD

USA CODE	94018567	RC (IN)	94.6
SW (IN)	10.4	RIM REC	9.00
OD (IN)	30.9	ECE	E4-106R-001812
SLR (IN)	14.2	PR	10

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	57
5 FR	4780
15 FR	4070
20 FR	3820
25 FR	3420
5 DW	3360
15 DW	2850
20 DW	2690
25 DW	2400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.