


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>540/65 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COSECHADORA / ESPARCIDOR / TRACTOR / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	142 D ; 145 AB



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94053704	<b>RC (IN)</b>	165.4
<b>SW (IN)</b>	20.9	<b>RIM REC</b>	W 16 L
<b>OD (IN)</b>	55.6	<b>RIM ALT</b>	W 18 L
<b>SLR (IN)</b>	25.3	<b>ECE</b>	E11-106R-002980

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	3270	3860	4390	4920	5380	5840
30	3440	4060	4610	5160	5650	6140
25	3580	4220	4790	5380	5890	6390
20	3770	4440	5050	5650	6190	6720
5 LT	4400	5180	5890	6590	7220	7840
5 HT	3770	4440	5050	5650	6190	6720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.