

# EARTHMAX SR 46

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 27.00 R 49                                                                               |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | SABIT KAYA KAMYONU                                                                       |
| VERSION      | HEAT RESISTANT COMPOUND                                                                  |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 223 B                                                                                    |



## BOYUTLAR IS STANDARD

|          |           |             |    |
|----------|-----------|-------------|----|
| OD (MM)  | 2688      | RIM ALT     | -  |
| SLR (MM) | 1225      | TRA CODE    | E4 |
| RC (MM)  | 8165      | STAR RATING | ★★ |
| RIM REC  | 19.50/4.0 |             |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00  | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 20600 | 21800 | 22400 | 23000 | 23600 | 25000 | 25750 | 26500 | 27250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.