DATA SHEET

Ultimo aggiornamento 16-06-2026

AGRIMAX TURF RT 333

TIRE SIZE	**260/70 R 16**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	VENDEMMIATRICE / MACCHINA PER IL RACCOLTO DI FRUTTETI / TRATTORINO / TRATTORE / MIETITREBBIA
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	109 A8 ; 109 B

DIMENSIONI IS STANDARD

SW (MM)	258	**RIM REC**	W 8
OD (MM)	770	**RIM ALT**	W 8 L ; W 9
SLR (MM)	348	**ECE**	E11-106R-007158
RC (MM)	2287	**SRI**	370

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	485	560	640	725	805	890	970	1030
40	485	560	640	725	805	890	970	1030
30	520	600	690	775	865	955	1040	1105
10 LT	655	750	860	970	1085	1195	1305	1385
10 HT	520	600	690	775	865	955	1040	1105

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..