


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	<b>560/55 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKER / TRAILER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	162 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94067626	<b>RC (IN)</b>	142.3
<b>SW (IN)</b>	21.4	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	46.5	<b>RIM ALT</b>	17.00; 20.00
<b>SLR (IN)</b>	21.0	<b>ECE</b>	E11-106R-006972

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58	65	73
45	3630	4390	4860	5630	6390	7050	7730	8490	9060	9530
40	3980	4820	5350	6180	7020	7750	8490	9330	9950	10470
30	4820	5830	6470	7480	8500	9380	10270	11290	12050	12670
25	5410	6560	7260	8410	9550	10550	11540	12680	13540	14240
15	6290	7620	8440	9770	11090	12250	13400	14730	15720	16540
5	7160	8670	9620	11120	12630	13950	12580	16780	17910	18850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.