


# AS 504

<b>TIRE SIZE</b>	<b>10.0/75 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS DRIVE WHEEL</b>	123 A8
<b>LI/SS FREE ROLLING</b>	135 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	264	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	785	<b>ECE</b>	E4-106R-001823
<b>SLR (MM)</b>	360	<b>PR</b>	18
<b>RC (MM)</b>	2404	<b>SRI</b>	360

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>7.10</b>
10 FR	3050
25 FR	2595
30 FR	2440
40 FR	2180
10 DW	2170
25 DW	1845
30 DW	1735
40 DW	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.