


AGRIMAX ELOS

| | |
|---------------------|--|
| TIRE SIZE | 420/85 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ТРАКТОР-ТЯГАЧ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 139 A8/B |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94040810 | RC (IN) | 171.2 |
| SW (IN) | 17.2 | RIM REC | W 15 L |
| OD (IN) | 57.8 | RIM ALT | W 13 ; W 14 L |
| SLR (IN) | 26.2 | ECE | E4-106R-000768 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 2950 | 3440 | 3910 | 4400 | 4880 | 5350 |
| 25 | 2950 | 3440 | 3910 | 4400 | 4880 | 5350 |
| 20 | 3160 | 3680 | 4200 | 4720 | 5240 | 5740 |
| 5 LT | 3960 | 4610 | 5250 | 5900 | 6550 | 7910 |
| 5 HT | 3160 | 3680 | 4200 | 4720 | 5240 | 5740 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.