


AGRIMAX RT 765

| | |
|---------------------|--|
| TYRE SIZE | 620/70 R 42 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | SPECIAL |
| TYRE TYPE | TL |
| LI/SS | 166 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94063543 | RC (IN) | 228.4 |
| SW (IN) | 24.6 | RIM REC | DW 20 B |
| OD (IN) | 76.2 | RIM ALT | DW 18 L |
| SLR (IN) | 34.5 | ECE | E11-106R-005998 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|-------|-------|-------|-------|-------|
| 40 | 5500 | 6320 | 7250 | 8180 | 9120 | 10050 | 10990 | 11680 |
| 30 | 5780 | 6640 | 7620 | 8600 | 9580 | 10560 | 11540 | 12270 |
| 25 | 6020 | 6910 | 7940 | 8960 | 9990 | 11010 | 12040 | 12800 |
| 20 | 6320 | 7260 | 8330 | 9410 | 10480 | 11560 | 12630 | 13440 |
| 5 LT | 7360 | 8470 | 9720 | 10970 | 12220 | 13480 | 14730 | 15660 |
| 5 HT | 6320 | 7260 | 8330 | 9410 | 10480 | 11560 | 12630 | 13440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.