


AGRIMAX FORCE



| | |
|---------------------|--|
| TYRE SIZE | IF 710/60 R 34 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HIGH-POWER TRACTOR / TRACTOR |
| VERSION | SPECIAL |
| TYRE TYPE | TL |
| LI/SS | 170 D |

DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|-----------------|----------------|
| USA CODE | 94060061 | RC (IN) | 201.8 |
| SW (IN) | 27.9 | RIM REC | DW 25 B |
| OD (IN) | 67.6 | ECE | E4-106R-001485 |
| SLR (IN) | 30.0 | TRA CODE | R1W |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 5530 | 6370 | 7340 | 8180 | 9140 | 9990 | 11190 | 12040 |
| FROM 40 TO 25 | 6080 | 7010 | 8070 | 8990 | 10050 | 10980 | 12300 | 13200 |
| 20 | 6330 | 7290 | 8390 | 9350 | 10450 | 11410 | 12790 | 13760 |
| 12 | 6570 | 7560 | 8710 | 9710 | 10850 | 11850 | 13280 | 14290 |
| 5 | 7730 | 8900 | 10240 | 11420 | 12760 | 13930 | 15620 | 16800 |
| UPTO 20 CYC | 7900 | 9100 | 10480 | 11680 | 13060 | 14260 | 15980 | 17200 |
| UPTO 10 CYC | 9420 | 10860 | 12500 | 13930 | 15570 | 17010 | 19060 | 20500 |
| UPTO 5 CYC | 10340 | 11920 | 13710 | 15290 | 17080 | 18660 | 20910 | 22490 |
| 5 HT | 6330 | 7290 | 8390 | 9350 | 10450 | 11410 | 12790 | 13760 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.