

# AGRIMAX RT 955

|                  |                                                                               |
|------------------|-------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>230/95 R 42</b>                                                            |
| <b>UM</b>        | IS STANDARD                                                                   |
| <b>MACHINERY</b> | PULVÉRISATEUR / MACHINE À<br>VENDANGER / MOISSONNEUSE /<br>OUTILLAGE AGRICOLE |
| <b>VERSION</b>   | STANDARD                                                                      |
| <b>TIRE TYPE</b> | TL                                                                            |
| <b>LI/SS</b>     | 133 A8/B                                                                      |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 228  | <b>RIM REC</b> | W 7            |
| <b>OD (MM)</b>  | 1506 | <b>RIM ALT</b> | W 8            |
| <b>SLR (MM)</b> | 714  | <b>ECE</b>     | E4-106R-000772 |
| <b>RC (MM)</b>  | 4595 | <b>SRI</b>     | 725            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  |
|------------|-----|------|------|------|------|------|------|------|------|------|
| 50         | 805 | 1055 | 1280 | 1405 | 1485 | 1630 | 1775 | 1920 | 2060 | -    |
| 40         | 805 | 1055 | 1280 | 1405 | 1485 | 1630 | 1775 | 1920 | 2060 | -    |
| 30         | 860 | 1125 | 1370 | 1500 | 1590 | 1745 | 1900 | 2055 | 2205 | -    |
| 10         | 960 | 1210 | 1485 | 1765 | 2040 | 2105 | 2350 | 2600 | 2845 | 3090 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.