

# FL 635

**650/55 R 22.5**

<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BALYA MAKINESI / BIÇERDÖVER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	167 D



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	645	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1287	<b>ECE</b>	E4-106R-000803
<b>SLR (MM)</b>	568	<b>SRI</b>	600
<b>RC (MM)</b>	3901		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1590	1815	2035	2530	2880	3325	3770	4120	4515	4960
65	1745	1990	2235	2780	3165	3655	4145	4525	4960	5450
50	2115	2410	2705	3365	3830	4420	5015	5475	6005	6595
40	2375	2710	3045	3785	4305	4970	5640	6155	6750	7415
25	2760	3150	3535	4395	5000	5775	6550	7155	7840	8615
10	3140	3585	4025	5005	5690	6575	7460	8145	8930	9810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.