


AGRIMAX V- FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 650/75 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTEUR DE FORTE PUISSANCE / TRACTEUR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 175 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| CODE USA | 94512164 | RC (IN) | 228.2 |
| SW (IN) | 26.6 | RIM REC | DW 23 B |
| OD (IN) | 76.4 | RIM ALT | DW 21 B |
| SLR (IN) | 32.8 | ECE | E11-106R-0010663 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|--------------------------------------|-------|-------|-------|-------|-------|-------|
| 45 | 7610 | 8850 | 10100 | 11340 | 12590 | 13830 |
| FROM 40 TO 25 | 8370 | 9730 | 11100 | 12470 | 13830 | 15210 |
| 20 | 8520 | 9920 | 11320 | 12710 | 14110 | 15510 |
| 12 | 8700 | 10120 | 11540 | 12960 | 14380 | 15820 |
| 5 | 9190 | 10700 | 12210 | 13710 | 15220 | 16730 |
| *UPTO 5 CYC WITH FRONT LOADER | 11710 | 13620 | 15540 | 17460 | 19380 | 21300 |
| 5 HT | 8520 | 9920 | 11320 | 12710 | 14110 | 15510 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.