

# TR 144

|                     |                         |
|---------------------|-------------------------|
| <b>TIRE SIZE</b>    | 9.5 - 22                |
| <b>UM</b>           | IS STANDARD             |
| <b>CONSTRUCTION</b> | ⊠ BIAS                  |
| <b>MACHINERY</b>    | SMALL TRACTOR / TRACTOR |
| <b>VERSION</b>      | STANDARD                |
| <b>TIRE TYPE</b>    | TT                      |
| <b>LI/SS</b>        | 104 A6                  |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 235  | <b>RIM REC</b> | W 8             |
| <b>OD (MM)</b>  | 1000 | <b>RIM ALT</b> | W 7             |
| <b>SLR (MM)</b> | 464  | <b>ECE</b>     | E11-106R-003485 |
| <b>RC (MM)</b>  | 3008 | <b>PR</b>      | 6               |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.20</b> |
| 30                | 900         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.