

# PL 801

**18X7 - 8**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	KUYRUK MILINE BAĞLI MAKINE / BIÇERDÖVER / FORKLIFT / BIÇERDÖVER / UYGULAMALI MAKINE / FORKLIFT
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
	121 A8



## UNDEFINED US STANDARD

<b>USA CODE</b>	94006977	<b>RIM ALT</b>	5.00 F
<b>SW (IN)</b>	6.8	<b>ECE</b>	E11-106R-003642
<b>OD (IN)</b>	18.5	<b>PR</b>	16
<b>RIM REC</b>	4.33 R		

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>145</b>
<b>15 LOAD WHEEL</b>	4730
<b>15 STEER WHEEL</b>	3635
<b>5 OTHER VEHICLES</b>	4730
<b>15 OTHER VEHICLES</b>	3635
<b>STATIC SIDE LOADER</b>	5490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.