

# MT 612

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 16.0/70 - 20   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | REMORCĂ / MAȘINI DE<br>IMPLEMENTARE / VEHICUL<br>UNIVERSAL |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |



## DIMENSIUNI US STANDARD

|                 |          |                |         |
|-----------------|----------|----------------|---------|
| <b>USA CODE</b> | 94035922 | <b>RC (IN)</b> | 131.0   |
| <b>SW (IN)</b>  | 15.9     | <b>RIM REC</b> | 13.00 T |
| <b>OD (IN)</b>  | 43.1     | <b>PR</b>      | 16      |
| <b>SLR (IN)</b> | 20.5     |                |         |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>65</b> |
| 50 LS            | 6780      |
| 50 LD            | 6010      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.