

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>520/70 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	148 D



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1640	<b>RIM ALT</b>	W 15 L; W 18 L
<b>SLR (MM)</b>	739	<b>ECE</b>	E11-106R-005831
<b>RC (MM)</b>	4927	<b>SRI</b>	775

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	1735	2020	2300	2585	2870	3150
50	1825	2120	2420	2715	3140	3310
40	1900	2210	2520	2830	3140	3450
30	1995	2320	2650	2975	3300	3625
10 LT	2325	2705	3085	3465	3845	4225
10 HT	1995	2320	2650	2975	3300	3625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.