


# MULTIMAX MP 527

<b>TYRE SIZE</b>	<b>480/80 R 26 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	160 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94055012	<b>RC (IN)</b>	167.7
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	DW 15 L
<b>OD (IN)</b>	56.2	<b>RIM ALT</b>	DW 16 L
<b>SLR (IN)</b>	25.3	<b>ECE</b>	E11-106R-004069

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	23	29	32	35	38	41	44	46	49	52
30	5750	6750	7340	7840	8330	8830	9420	9920	-	-
25	5750	6750	7340	7840	8330	8830	9420	9920	-	-
20	6160	7220	7860	8390	8920	9460	10090	10610	-	-
15	6390	7500	8160	8710	9260	9810	10470	11010	-	-
5 CYC.	7000	8630	9380	10120	11010	11760	12500	13390	14140	14880
STATIC	10720	13240	14380	15520	16890	18030	19170	20530	21680	22820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.