

RIDEMAX FL 615

TIRE SIZE	VF 800/65 R 32
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ПРИЦЕП / АВТОЦИСТЕРНА / РАЗБРАСЫВАТЕЛЬ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	190 D



РАЗМЕРЫ IS STANDARD

SW (MM)	815	RIM REC	DW 28 B
OD (MM)	1850	RIM ALT	DW 27 B
SLR (MM)	811	ECE	E11-106R-0010408
RC (MM)	5610	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8
65	5195	5830	7105	8060	9330	10600
50	6080	6825	8315	9430	10920	12405
40	6705	7525	9165	10395	12035	13675
30	7330	8225	10020	11365	13160	14950
25	7590	8515	10375	11765	13625	15480
20	7900	8865	10800	12250	14185	16115
10	8520	9565	11650	13215	15300	17385

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.