


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>320/65 R 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VENDIMIADORA / TRACTOR / COSECHADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	117 D ; 120 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	319	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	822	<b>RIM ALT</b>	W 9 ; W 11
<b>SLR (MM)</b>	366	<b>ECE</b>	E4-106R-001815
<b>RC (MM)</b>	2466	<b>SRI</b>	390

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	605	710	810	900	990	1070	1185	1285
<b>50</b>	635	745	855	945	1040	1125	1245	1350
<b>40</b>	660	770	885	980	1080	1165	1290	1400
<b>30</b>	700	815	935	1040	1140	1230	1365	1480
<b>10 LT</b>	815	950	1090	1210	1330	1435	1590	1725
<b>10 HT</b>	700	815	935	1040	1140	1230	1365	1480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.