

# AGRIMAX RT 855

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 320/85 R 28                                                                              |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA          |
| VERSIÓN      | STANDARD                                                                                 |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 124 A8/B                                                                                 |



## DIMENSIONES US STANDARD

|            |          |         |                |
|------------|----------|---------|----------------|
| CÓDIGO USA | 94021574 | RC (IN) | 147.4          |
| SW (IN)    | 13.0     | RIM REC | W 11           |
| OD (IN)    | 49.4     | RIM ALT | W 9 ; W 10     |
| SLR (IN)   | 22.4     | ECE     | E4-106R-000615 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 1940 | 2260 | 2580 | 2900 | 3220 | 3520 |
| 25        | 1940 | 2260 | 2580 | 2900 | 3220 | 3520 |
| 20        | 2080 | 2420 | 2770 | 3110 | 3450 | 3780 |
| 5 LT      | 2600 | 3030 | 3460 | 3880 | 4310 | 4730 |
| 5 HT      | 2080 | 2420 | 2770 | 3110 | 3450 | 3780 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.