

# AW 702

<b>TIRE SIZE</b>	12.5/80 - 15.3
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / REBOQUE
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	144 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94045273	<b>RC (IN)</b>	102.1
<b>SW (IN)</b>	12.3	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	34.8	<b>ECE</b>	E11-106R-004355
<b>SLR (IN)</b>	15.2	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>71</b>
5 FR	8640
15 FR	7340
20 FR	6910
25 FR	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.