

# TR 882

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>400/60 - 15.5</b>   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | BALER / HAY HARVESTER /<br>IMPLEMENT MACHINERY / TRAILER /<br>HARVESTER / IMPLEMENTS / TRAILER |
| <b>VERSION</b>            | SPECIAL  |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 132 A8   |
| <b>LI/SS FREE ROLLING</b> | 145 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 400  | <b>RIM REC</b> | AG 13.00        |
| <b>OD (MM)</b>  | 875  | <b>ECE</b>     | E11-106R-004332 |
| <b>SLR (MM)</b> | 378  | <b>PR</b>      | 14              |
| <b>RC (MM)</b>  | 2605 | <b>SRI</b>     | 410             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.60 |
|------------|------|
| 10 FR      | 4060 |
| 25 FR      | 3450 |
| 30 FR      | 3250 |
| 40 FR      | 2900 |
| 10 DW      | 2800 |
| 25 DW      | 2380 |
| 30 DW      | 2240 |
| 40 DW      | 2000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.