


MULTIMAX MP 522

TYRE SIZE	380/75 R 20 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
VERSION	STANDARD
TL/TT	TL
LI/SS	148 A8/B



DIMENSIONS US STANDARD

USA CODE	94045877	RC (IN)	128.0
SW (IN)	15.1	RIM REC	W 12
OD (IN)	42.3	RIM ALT	W 11 ; 11 ; 12
SLR (IN)	19.0	ECE	E11-106R-002963

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	23	29	35	41	46	52	55	58	61	64
30	3310	3900	4500	5080	5680	6310	6620	6940	-	-
25	3310	3900	4500	5080	5680	6310	6620	6940	-	-
20	3550	4190	4840	5490	6130	6780	7100	7430	-	-
15	3680	4350	5030	5700	6370	7040	7390	7720	-	-
5 CYC.	4080	4980	5890	6790	7690	8600	9060	9510	9960	10430
STATIC	6260	7650	9040	10430	11820	13210	13900	14590	15290	15980

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.