


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 280/85 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 118 A8/B |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CODICE USA | 94021543 | RC (IN) | 140.1 |
| SW (IN) | 11.5 | RIM REC | W 10 |
| OD (IN) | 46.7 | RIM ALT | W 9 |
| SLR (IN) | 21.5 | ECE | E4-106R-000614 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 1610 | 1860 | 2130 | 2390 | 2660 | 2910 |
| 25 | 1610 | 1860 | 2130 | 2390 | 2660 | 2910 |
| 20 | 1720 | 2010 | 2280 | 2570 | 2840 | 3120 |
| 5 LT | 2150 | 2500 | 2850 | 3210 | 2560 | 3900 |
| 5 HT | 1720 | 2010 | 2280 | 2570 | 2840 | 3120 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.