

# FARM 2000

<b>TIRE SIZE</b>	<b>300/80 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	120 A8
<b>LI/SS FREE ROLLING</b>	132 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94034673	<b>RC (IN)</b>	102.7
<b>SW (IN)</b>	11.8	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	35.0	<b>ECE</b>	E11-106R-003517
<b>SLR (IN)</b>	15.3		

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>41</b>
<b>5 FR</b>	6170
<b>15 FR</b>	5250
<b>20 FR</b>	4940
<b>25 FR</b>	4410
<b>5 DW</b>	4320
<b>15 DW</b>	3670
<b>20 DW</b>	3460
<b>25 DW</b>	3090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.