

# FLOTATION 558

	<b>400/55 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALYA MAKINESI / BIÇERDÖVER / TANKER / RÖMORK / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	138 A8/134 B
	150 A8/146 B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94006243	<b>RC (IN)</b>	121.4
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	AG 11.75
<b>OD (IN)</b>	40.2	<b>RIM ALT</b>	12.25; 13.00; AG 13.00
<b>SLR (IN)</b>	17.5	<b>ECE</b>	E4-106R-002261

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44	46	51
5 FR	9450	9810	10340
10 FR	8500	8830	9300
20 FR	7550	7850	8270
25 FR	6750	7010	7390
30 FR	6070	6300	6610
5 DW	6650	6910	7290
10 DW	5990	6220	6560
20 DW	5320	5530	5830
25 DW	4750	4940	5200
30 DW	4280	4440	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.