


AGRIMAXFACTOR

| | |
|---------------------|--|
| TIRE SIZE | 620/70 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATTORE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 160 D ; 163 A8 |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 625 | RIM REC | DW 20 B |
| OD (MM) | 1935 | RIM ALT | DW18L ; W18L |
| SLR (MM) | 863 | ECE | E11-106R-007764 |
| RC (MM) | 5786 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 2475 | 2880 | 3285 | 3690 | 4095 | 4500 |
| 50 | 2600 | 3025 | 3450 | 3875 | 4300 | 4725 |
| 40 | 2715 | 3160 | 3600 | 4045 | 4490 | 4930 |
| 30 | 2850 | 3315 | 3780 | 4245 | 4710 | 5175 |
| 10 LT | 3320 | 3860 | 4405 | 4945 | 5490 | 6030 |
| 10 HT | 2850 | 3315 | 3780 | 4245 | 4710 | 5175 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.