


MULTIMAX MP 527

TIRE SIZE	460/70 R 24 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	KOMPAKTHJULLASTARE / TELESKOPLASTARE / KOMPAKTHJULLASTARE / TELESKOPLASTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	159 A8/B



DIMENSIONER IS STANDARD

SW (MM)	465	RIM REC	DW 15 L
OD (MM)	1254	RIM ALT	DW 14 L ; DW 16 L
SLR (MM)	574	ECE	E11-106R-002983
RC (MM)	3801	SRI	600

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2100	2495	2845	3240	3635	3895	4375	-	-
40	2100	2495	2845	3240	3635	3895	4375	-	-
30	2250	2675	3050	3470	3890	4170	4685	-	-
25	2335	2775	3160	3600	4035	4330	4860	-	-
10 CYC.	2565	3155	3710	4270	4860	5285	5975	6305	6565
STATIC	3930	4835	5690	6545	7450	8105	9160	9665	10065

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.