


# RIDEMAX FL 690

<b>TIRE SIZE</b>	<b>800/60 R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKBIL / SLÄPVAGN / ARBETSFORDON / SLÄPVAGN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	185 D



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94066254	<b>RC (IN)</b>	214.7
<b>SW (IN)</b>	31.5	<b>RIM REC</b>	DH 27 B
<b>OD (IN)</b>	70.9	<b>RIM ALT</b>	DW 27 B
<b>SLR (IN)</b>	32.2	<b>ECE</b>	E11-106R-006480

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58
45	5940	7620	9470	10770	12440	14110	15410	16900	18560
40	6530	8370	10410	11830	13670	15500	16930	18560	20390
30	7900	10120	12590	14320	16540	18760	20490	22460	24680
25	8880	11380	14150	16090	18580	21090	23030	25240	27730
20	9870	12630	15710	17870	20630	23410	25570	28030	30800
15	10320	13220	16430	18690	21590	24490	26750	29320	32220
5	11750	15060	18730	21300	24600	27900	30470	33410	36700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.