

# AGRIMAX RT 855

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>380/85 R 24</b>                                                              |
| <b>UM</b>        | US STANDARD                                                                     |
| <b>MACHINERY</b> | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>   | SPECIAL                                                                         |
| <b>TIRE TYPE</b> | TL                                                                              |
| <b>LI/SS</b>     | 131 A8/B                                                                        |

## DIMENSIONES US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CÓDIGO USA</b> | 94044672 | <b>RC (IN)</b> | 146.5          |
| <b>SW (IN)</b>    | 15.0     | <b>RIM REC</b> | W 12           |
| <b>OD (IN)</b>    | 49.4     | <b>RIM ALT</b> | W 11 ; W 13    |
| <b>SLR (IN)</b>   | 21.8     | <b>ECE</b>     | E4-106R-000592 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 2370 | 2760 | 3140 | 3530 | 3910 | 4300 |
| <b>25</b>   | 2370 | 2760 | 3140 | 3530 | 3910 | 4300 |
| <b>20</b>   | 2540 | 2950 | 3370 | 3780 | 4200 | 4610 |
| <b>5 LT</b> | 3170 | 3690 | 4210 | 4730 | 5250 | 5760 |
| <b>5 HT</b> | 2540 | 2950 | 3370 | 3780 | 4200 | 4610 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

