


RIDEMAX FL 693 M



| | |
|---------------------|--|
| TIRE SIZE | 650/55 R 26.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE |
| VERSION | HD |
| TIRE TYPE | TL |
| LI/SS | 178 D |

DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94049622 | RC (IN) | 167.3 |
| SW (IN) | 25.4 | RIM REC | AG 20.00 |
| OD (IN) | 54.7 | ECE | E11-106R-003008 |
| SLR (IN) | 24.2 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 73 | 87 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40 | 5130 | 6120 | 7440 | 8600 | 9920 | 11240 | 12070 | 13390 | 14720 | 15540 | 16530 |
| 30 | 6210 | 7410 | 9010 | 10410 | 12000 | 13610 | 14600 | 16210 | 17810 | 18820 | 20010 |
| 25 | 6980 | 8320 | 10120 | 11690 | 13490 | 15300 | 16420 | 18220 | 20020 | 21140 | 22490 |
| 20 | 7750 | 9250 | 11240 | 12980 | 14980 | 16990 | 18230 | 20230 | 22220 | 23480 | 24970 |
| 15 | 8100 | 9670 | 11760 | 13590 | 15670 | 17770 | 19080 | 21160 | 23260 | 24560 | 26120 |
| 5 | 9230 | 11010 | 13390 | 15480 | 17860 | 20240 | 21730 | 24110 | 26490 | 27980 | 29760 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.