


AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 7.50 - 20 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 103 A8 |
| LI/SS FREE ROLLING | 116 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|------------------------|
| SW (MM) | 209 | RIM REC | 5.50 F |
| OD (MM) | 904 | RIM ALT | 4.50 E; 6.00 F; 5.00 F |
| SLR (MM) | 422 | ECE | E4-106R-002636 |
| RC (MM) | 2695 | PR | 8 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.20 |
|------------|------|
| 10 FR | 1750 |
| 25 FR | 1490 |
| 30 FR | 1400 |
| 40 FR | 1250 |
| 10 DW | 1225 |
| 25 DW | 1040 |
| 30 DW | 980 |
| 40 DW | 875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.