


RM 500

| | |
|---------------------|--|
| TIRE SIZE | 600/65 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE RECOLTARE |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 177 A8 ; 165 A8 |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 590 | RIM REC | W 18 L |
| OD (MM) | 1486 | RIM ALT | W 20 L |
| SLR (MM) | 640 | ECE | E11-106R-007699 |
| RC (MM) | 4340 | SRI | 700 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 |
|------------------------|------|------|------|------|------|------|------|
| 40 FREE ROLLING | 3070 | 3505 | 3945 | 4820 | 5550 | 6425 | 7300 |
| 40 DRIVE WHEEL | 2165 | 2475 | 2785 | 3400 | 3915 | 4535 | 5150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.