

# AGRIMAX FORCE

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | IF 800/70 R 42 CFO                                                                       |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | HARVESTER / HIGH-POWER TRACTOR<br>/ TRACTOR                                              |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 186 D                                                                                    |



## DIMENSIONS US STANDARD

|          |          |         |                           |
|----------|----------|---------|---------------------------|
| USA CODE | 94073641 | RC (IN) | 252.0                     |
| SW (IN)  | 31.3     | RIM REC | DW 27 B                   |
| OD (IN)  | 84.6     | RIM ALT | DW 25 B, DW 28 B, DW 30 B |
| SLR (IN) | 37.4     | ECE     | E4-106R-002650            |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 8950  | 10280 | 11810 | 13340 | 14860 | 16380 | 17910 | 19060 |
| FROM 40 TO 25 | 9840  | 11310 | 12980 | 14660 | 16340 | 18010 | 19690 | 20900 |
| 20            | 10230 | 11760 | 13500 | 15240 | 16990 | 18730 | 20470 | 21780 |
| 12            | 10630 | 12210 | 14020 | 15830 | 17640 | 19440 | 21250 | 22620 |
| 5             | 12500 | 14360 | 16490 | 18620 | 20740 | 22870 | 25000 | 26600 |
| UPTO 20 CYC   | 12790 | 14690 | 16880 | 19060 | 21230 | 23410 | 25580 | 27230 |
| UPTO 10 CYC   | 15260 | 17530 | 20120 | 22720 | 25320 | 27910 | 30510 | 32460 |
| UPTO 5 CYC    | 16730 | 19220 | 22070 | 24920 | 27770 | 30610 | 33460 | 35600 |
| 5HT           | 10230 | 11760 | 13500 | 15240 | 16990 | 18730 | 20470 | 21780 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.