


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>650/65 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINDIMADORA / TRATOR / CEIFEIRA
<b>VERSÃO</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 A8 ; 175 B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94074853	<b>RC (IN)</b>	216.1
<b>SW (IN)</b>	25.4	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	71.5	<b>RIM ALT</b>	DW 21 B; DW 23 B
<b>SLR (IN)</b>	32.6	<b>ECE</b>	E11-106R-008886

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>51</b>
30	15190
25	16540
20	17710
15	18370
5	24810
<b>STATIC</b>	38030
5 LT	23150
12 LT	19850
5 HT	17710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.