


AW 712

| | |
|---------------------|--|
| TIRE SIZE | 260/70 R 15.3 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAQUINARIA AGRÍCOLA / PULVERIZADOR / MAQUINARIA AGRÍCOLA |
| VERSIÓN | IMPLEMENT |
| TIRE TYPE | TL |
| LI/SS | 134 A8/B |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|------------------|
| CÓDIGO USA | 94059584 | RC (IN) | 90.7 |
| SW (IN) | 10.4 | RIM REC | 9.00 |
| OD (IN) | 29.9 | ECE | 'E11-106R-005096 |
| SLR (IN) | 13.5 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 58 | 73 |
|-----------|------|------|------|------|------|------|------|------|------|------|------|
| 30 | 1360 | 1730 | 2110 | 2440 | 2810 | 3190 | 3420 | 3790 | 3920 | 4400 | 4670 |
| 25 | 1360 | 1730 | 2110 | 2440 | 2810 | 3190 | 3420 | 3790 | 3920 | 4400 | 4670 |
| 20 | 1520 | 1940 | 2360 | 2720 | 3140 | 3560 | 3820 | 4240 | 4390 | 4930 | 5240 |
| 15 | 1620 | 2060 | 2510 | 2900 | 3340 | 3790 | 4070 | 4520 | 4660 | 5240 | 5570 |
| 10 | 1720 | 2180 | 2660 | 3080 | 3540 | 4010 | 4310 | 4780 | 4940 | 5540 | 5900 |
| 5 | 1910 | 2420 | 2950 | 3410 | 3940 | 4450 | 4780 | 5310 | 5490 | 6160 | 6550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.