

AGRIMAX RT 765

TIRE SIZE	620/70 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVÉRISATEUR / TRACTEUR / MACHINE À VENDANGER / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	170 D



DIMENSIONS IS STANDARD

SW (MM)	625	RIM REC	DW 20 B
OD (MM)	1833	RIM ALT	DW 18 L ; W 18 L
SLR (MM)	828	ECE	E11-106R-005997
RC (MM)	5591	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
65	2340	2760	3180	3540	3960	4320	4740	5100	5580	6000
50	2460	2900	3340	3720	4160	4540	4980	5355	5860	6300
40	2565	3025	3485	3880	4340	4735	5195	5585	6155	6570
30	2695	3175	3660	4075	4555	4970	5455	5865	6420	6900
10 LT	3140	3700	4265	4745	5310	5790	6355	6835	7480	8040
10 HT	2695	3175	3660	4075	4555	4970	5455	5865	6420	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.