


# AGRIMAX FORCE



<b>TIRE SIZE</b>	<b>IF 750/75 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	186 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	742	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	2294	<b>ECE</b>	E11-106R-006491
<b>SLR (MM)</b>	1032	<b>SRI</b>	1075
<b>RC (MM)</b>	6802	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	4060	4665	5355	6050	6740	7430	8125	8645
<b>FROM 65 TO 40</b>	4465	5130	5890	6650	7410	8170	8930	9500
30	4640	5335	6125	6915	7705	8495	9285	9880
20	4820	5540	6360	7180	8000	8820	9640	10260
10	5670	6515	7480	8445	9410	10370	11340	12065
<b>UPTO 30 CYC</b>	5800	6665	7655	8645	9630	10620	11605	12350
<b>UPTO 15 CYC</b>	6920	7950	9125	10305	11485	12660	13840	14725
<b>UPTO 10 CYC</b>	7590	8720	10010	11305	12595	13885	15180	16150
10HT	4640	5335	6125	6915	7705	8495	9285	9880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.