


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>IF 1250/50 R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN / SPRIDARE / TRAKTOR / ARBETSFORDON
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	201 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94068876	<b>RC (IN)</b>	241.6
<b>SW (IN)</b>	49.1	<b>RIM REC</b>	DH44B/1.3 (multi-piece)
<b>OD (IN)</b>	81.2	<b>ECE</b>	E11-106R-006958
<b>SLR (IN)</b>	35.3		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46	49	55
30	14380	16300	20460	22700	25250	27170	29730	31970	---	---
25	15690	17780	22310	24750	27530	29620	32140	34840	---	---
20	16790	19020	23870	26480	29460	31700	34690	37290	---	---
5 LT	21020	23820	29890	33160	36890	39690	43430	46690	---	---
5 HT	16790	18020	23870	26480	29460	31700	34690	37290	---	---
<b>UPTO 5 CYC WITH FRONT LOADER</b>	---	26370	33770	37020	42950	47100	51540	55980	56880	59230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.