

FLOTATION 648

TIRE SIZE	385/65 - 22.5
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	144 A8/140 B
LI/SS FREE ROLLING	156 A8/152 B



DIMENSIONER US STANDARD

USA CODE	94006281	RC (IN)	127.3
SW (IN)	15.7	RIM REC	AG 11.75
OD (IN)	42.1	ECE	E4-106R-002335
SLR (IN)	18.7	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	36	51
5 FR	7520	10140	12350
10 FR	6770	9130	11110
20 FR	6010	8110	9880
25 FR	5370	7240	8820
30 FR	4830	6510	7830
5 DW	5260	7100	8640
10 DW	4740	6390	7780
20 DW	4210	5680	6910
25 DW	3760	5070	6170
30 DW	3380	4560	5510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.