


AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 440/65 R 24 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 135 D ; 138 A8 |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 441 | RIM REC | W 14 L |
| OD (MM) | 1182 | RIM ALT | W 13; W 15 L |
| SLR (MM) | 538 | ECE | E4-106R-000616 |
| RC (MM) | 3546 | SRI | 575 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|--------------|------|------|------|------|------|------|------|------|
| 65 | 1050 | 1225 | 1375 | 1530 | 1680 | 1810 | 2010 | 2180 |
| 50 | 1100 | 1285 | 1445 | 1605 | 1765 | 1905 | 2110 | 2290 |
| 40 | 1135 | 1325 | 1490 | 1655 | 1820 | 1960 | 2175 | 2360 |
| 30 | 1205 | 1410 | 1585 | 1760 | 1935 | 2085 | 2310 | 2510 |
| 10 LT | 1405 | 1640 | 1845 | 2050 | 2255 | 2430 | 2695 | 2925 |
| 10 HT | 1205 | 1410 | 1585 | 1760 | 1935 | 2085 | 2310 | 2510 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.