

AS 504

15.5/80 - 24

| | |
|---------------------|---|
| UM | IS STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | TELESKOPIK YÜKLEYİCİ / TARLA RÖMORKU / UYGULAMALI MAKİNE / TELESKOPIK YÜKLEYİCİ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 148 A8 |
| | 160 A8 |



UNDEFINED IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 384 | RIM REC | W 12 |
| OD (MM) | 1262 | RIM ALT | W 13; W 14 L |
| SLR (MM) | 570 | ECE | E4-106R-002816 |
| RC (MM) | 3875 | PR | 14 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.50 |
|------------|------|
| 10 FR | 6300 |
| 25 FR | 5355 |
| 30 FR | 5040 |
| 40 FR | 4500 |
| 10 DW | 4410 |
| 25 DW | 3750 |
| 30 DW | 3530 |
| 40 DW | 3150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.