


FL 630 SUPER

| | |
|---------------------|--|
| TIRE SIZE | 850/50 R 30.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE ÎMPRĂȘTIAT / CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 182 D |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94073191 | RC (IN) | 192.7 |
| SW (IN) | 33.9 | RIM REC | AG 28.00 |
| OD (IN) | 64.0 | ECE | E11-106R-008232 |
| SLR (IN) | 28.4 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 7000 | 8700 | 9900 | 11430 | 12960 | 14160 | 15520 | 17050 |
| 40 | 7680 | 9560 | 10870 | 12550 | 14240 | 15550 | 17050 | 18740 |
| 30 | 9300 | 11570 | 13160 | 15200 | 17240 | 18830 | 20630 | 22670 |
| 25 | 10450 | 13010 | 14780 | 17080 | 19380 | 21150 | 23190 | 25480 |
| 15 | 12150 | 15100 | 17170 | 19840 | 22510 | 24580 | 26950 | 29610 |
| 5 | 13830 | 17210 | 19560 | 22610 | 25640 | 28000 | 30700 | 33730 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.